

Web Lanyard with SofStop

Model: 913WLS

Description

The 913WLS with SofStop shock-absorber is designed to reduce fall arrest forces.

The integral SofStop shock-absorber has a specially-woven inner core that smoothly deploys during a fall arrest.

Materials

Webbing

Lanyard:	1 in. polyester
Shock-absorbing web core:	polyester
Safety strap:	1-1 ¾ in. polyester
Thread:	6 cord bonded 3 strand polyester thread with a min. tensile of 42 lbs.
Hardware:	Steel
Snap Hooks:	5,000 lb (22kN), 3/4 in. (19mm) gate opening.
Label:	Lexan and Valeron

* All hardware meets ASTM (50) fifty-hour salt spray test requirements.



913WLS

Technical

Max. Working Load:	310 lbs (141kg)
Min. Tensile (webbing):	5,000 lbs (0.31kg)

Certification

Meets applicable OSHA, ANSI and CSA requirements.



Toll Free 800-873-5242 • Phone 814.432.2118 • Fax 814.437.2973 • www.millerfallprotection.com

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM MILLER FALL PROTECTION AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. MILLER FALL PROTECTION RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.