

Titan™ Tubular Shock Absorbing Lanyards

Description

Titan Tubular shock-absorbing lanyards feature a built-in woven inner core which smoothly expands 3 ½ ft (1.1m) to reduce fall arrest forces, while the outer jacket serves as a back-up web lanyard.

Materials

Webbing

Safety Strap/Jacket: Yellow tubular polyester webbing

Shock Absorbing

Web Core: Polyester

Thread: 6 cord bonded 3 strand polyester thread with a min. tensile of 42 lbs.

Hardware:

Locking Snap Hooks: 5,000 lb (22kN), 3/4 in.

Label: Valeron

* All hardware meets ASTM (50) fifty-hour salt spray test requirements.



T5112/6FT
shown

Technical

Max. Working Load: 310 lbs (141kg)

Min. Tensile (webbing): 5,000 lbs (0.31kg)

Min. Tensile (snaps): 5,000 lbs (0.31kg)

Certification

Meets applicable OSHA, ANSI and CSA requirements.

Model No.	No. of Legs	Harness Connection	Anchorage Connection	Lanyard Length
T5011/6FT	One	Choke-Off Loop	Locking Snap Hook	6 ft. (1.8m)
T5111/6FT	One	Locking Snap Hook	Locking Snap Hook	6 ft. (1.8m)
T5112/6FT	One	Locking Snap Hook	Large Locking Rebar Hook	6 ft. (1.8m)
T5113/6FT	One	Locking Snap Hook	Small Locking Rebar Hook	6 ft. (1.8m)
T5121/6FT	Two	Locking Snap Hook	Locking Snap Hooks	6 ft. (1.8m)
T5122/6FT	Two	Locking Snap Hook	Large Locking Rebar Hooks	6 ft. (1.8m)
T5123/6FT	Two	Locking Snap Hook	Small Locking Rebar Hooks	6 ft. (1.8m)

Small Locking Rebar Hook (1-3/4" [44mm] gate opening). Large Locking Rebar Hook (2-1/4" [57mm] gate opening). Available from 4 ft. (1.2m) to 10 ft. (3m) lengths.



Toll Free 800-873-5242 • Phone 814.432.2118 • Fax 814.437.2973 • www.millerfallprotection.com

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM MILLER FALL PROTECTION AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. MILLER FALL PROTECTION RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.